

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>G09G 3/36</b>		A1	(11) International Publication Number: <b>WO 00/38167</b>
			(43) International Publication Date: 29 June 2000 (29.06.00)
(21) International Application Number: PCT/GB99/04275		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 16 December 1999 (16.12.99)			
(30) Priority Data: 9827945.8 19 December 1998 (19.12.98) GB			
(71) Applicant (for all designated States except US): THE SECRETARY OF STATE FOR DEFENCE [GB/GB]; Defence Research and Evaluation Agency, Ively Road, Farnborough, Hampshire GU14 0LX (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): CROSSLAND, William, Alden [GB/GB]; University of Cambridge, Engineering Dept., Trumpington Street, Cambridge CB2 1PZ (GB). YU, Tat, Chi, B. [-/-]; *		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(74) Agents: GODDARD, David, John; Harrison Goddard Foote, 1 Stockport Road, Marple, Stockport SK6 6BD (GB) et al.			

(54) Title: METHODS OF DRIVING AN ARRAY OF OPTICAL ELEMENTS

(57) Abstract

Relates to writing an array of optical elements which are each switched between two states according to input data sets. In a first method, data is written in two steps in which different selected elements are respectively driven to one binary state and the other binary state. The selected elements of the two sets may be complementary, but are preferably only those which are required to change from their existing state. The latter criterion may be used in an alternative method using a single addressing of the array to turn elements in either direction as required. In a further method, as shown, selected elements only of a blank array are written in a first WRITE step so as to correspond with a set of data, and in a subsequent second ERASE step the selected elements are selectively erased to restore a blank array prior to writing and erasing another set of data. The methods have particular utility for maintaining a dc balance at pixels of a liquid crystal array.

